




ELECTRA

Tall Tubular Batteries

Key Features

- Extremely high purity, corrosion resistant proprietary spine alloy composition ensures longer battery service life
- Tubular plate construction ensures uniform distribution of positive active material for extremely long life and superior performance
- Extra strong, flexible oxidation-resistant gauntlet for higher performance and extremely long life
- Plates specially designed for better charge acceptance



Tall tubular battery



42-48 months warranty*



Factory charged battery in ready to use condition



Long & tubular plates give more back-up & longer life



High durability with sealed plastic housing



Easy maintenance with level indicators

Technical Specifications

	Nominal Voltage (V)	Rated Capacity @ 27°C (Ah)	Dimensions of Container			Electrolyte Volume (Ltrs.)	Charging Current (Amp)				Weight (Kg.)		Water Level Indicator (No.)
			Length (mm)	Width (mm)	Height (mm)		Boost Mode		Trickle Mode		Dry	Filled	
							Starting Current	Finishing Current	Min (mA)	Max (mA)			
LETT 18000	12	145	503	189	362	18.00	14.10	7.10	122.0	487	28.0	48.5	6
LETT 15036	12	150	503	189	411	18.90	15.10	7.60	126.0	504	28.4	52.1	1
LE 18036TT	12	150	503	189	411	21.00	15.10	7.60	126.0	504	33.0	57.0	6
LE 578 TT	12	155	503	189	411	21.00	15.10	7.60	126.0	504	33.0	57.0	6
LE 568 TT	12	155	503	189	411	21.50	16.10	8.10	134.0	538	31.0	56.0	6
LE 590 TT	12	175	503	189	411	21.00	18.10	9.10	151.0	605	37.0	61.0	6
LETT 20060	12	200	503	189	411	21.30	20.20	10.10	168.0	672	38.5	64.8	6