



Inverlast SHORT TUBULAR BATTERIES

Key Features

- Extremely high purity, corrosion-resistant proprietary spine alloy composition ensures longer battery service life
- Tubular plate construction ensures uniform distribution of positive active material for extremely long life and superior performance
- Extra-strong, flexible oxidation-resistant gauntlet for higher performance and extremely long life
- Plates designed for improved charge acceptance



Short Tubular Battery



24-18 Months* Warranty



Factory charged battery in ready to use condition



Long & Tubular Plates give more back-up & longer life



Ideal for longer duration & frequent power cut areas



Easy maintenance with level indicators

Technical Specifications

Model	Nominal Voltage (V)	Rated Capacity @ 27°C (Ah)	Dimensions of Container			Electrolyte Volume (Ltrs.)	Charging Current (Amp)				Weight (Kg.)		Water Level Indication (No.)
			Length (mm)	Width (mm)	Height (mm)		Boost Mode		Trickle Mode		Dry	Filled	
							Starting Current	Finishing Current	Min (mA)	Max (mA)			
ILT 6000	12	60	410	176	233	7.70	6.00	3.00	50.4	201.6	13.3	22.8	6
LT 300	12	80	410	174	285	10.50	8.10	4.00	67.0	269.0	17.2	29.3	6
ILT 1224	12	100	505	220	292	17.00	10.10	5.00	84.0	336.0	17.0	39.0	6
ILT 14048XL	12	120	505	220	292	14.70	12.10	6.00	100.8	403.2	21.4	40.7	6
ILTJ 18030	12	150	517	272	288	21.60	15.10	7.60	126.0	504.0	30.5	56.9	6